## **Carat-S Garden Comfort Package**





## **Platin Garden Comfort package**

- Simple & quick to install
- Submersible pump supplies harvested rainwater on demand to external taps, internal and external hose connection boxes
- Water can be extracted using an internal and/or external hose connection box for standard irrigation purposes

## **Scope of supply**

- 1 Underground tank (choice of tanks available, sizes vary according to property type)
- 2 Telescopic lid (choice of telescopic lid available, depending on tank location)
- 3 Filter (Basket filter supplied in accordance with type of tank)
- 4 Submersible pump with floating water intake
- Internal hose connection box
- 6 External hose connection box

## Supplied by others

- 100mm diameter duct pipe to contain; power cable for pump
- 8 100mm diameter drainage pipe connected from downpipes to the inlet at the top of the tank (all downpipes brought into one pipe for connection to the filter)
- 100mm diameter pipe for overflow from the tank to mains drainage network

Dimensions/weight	2,700 litres (700 US gallons)	3,750 litres (1,000 US gallons)	4,800 litres (1,250 US gallons)	6,500 litres (1,700 US gallons)
Length (I)	2,080mm (81.9")	2,280mm (89.8")	2,280 (89.8")	2,390 (94.1")
Width (w)	1,565mm (61.6")	1,755mm (69.1")	1,985mm (78.2")	2,190mm (86.2")
Height (h)	2,010mm (79.12")	2,200mm (86.6")	2,430mm (95.65")	2,710mm (106.68")
Ø tank dome (d)	800mm (31.5")	800mm (31.5")	800mm (31.5")	800mm (31.5")
Weight	120kg	150kg	185kg	220kg



