

### Product Specification Sheet

Graf Platin tanks are manufactured from selected recyclable material and have the highest stability thanks to modern production methods. They are groundwater stable, can be installed at shallow depths and are suitable for vehicle loading (when combined with a vehicle loading lid). The Graf Platin tanks, feature a 25-year lifespan design, accompanied by a 10-year manufacturer's warranty for added assurance.

### Technical Specification

Tank	Product Code	Dimensions (mm) (with Dome)	Weight (kg) excluding lid	Connections
1,500L	G70007*/ G70008**	2100 x 1250 x 700 (1015)	82kg	DN100 (4")
3,000L	G70009*/ G70010**	2450 x 2100 x 735 (1050)	180kg	DN100 (4")
5,000L	G70011*/ G70012**	2890 x 2300 x 1000 (1315)	250kg	DN100 (4")
7,500L	G70013*/ G70014**	3600 x 2250 x 1250 (1565)	360kg	DN100 (4")

The stated tank heights are exclusive from the accessories below.  
\*Pedestrian Loading Lid \*\*Vehicle Loading Lid



### Tank Accessories Specification

Image	Item	Product Code	Weight (kg)	Diameter Ø	Min. Height (mm)	Max. Height (mm)	Max. Loading (kg)*
	Pedestrian Loading Lid (Mini)	371010	9kg	Ø 600mm	60mm	360mm	150kg
	Pedestrian Loading Lid (Maxi)	371011	15kg	Ø 600mm	60mm	476mm	150kg
	Vehicle Loading Lid	371020	22kg	Ø 625mm	60mm	476mm	3,500kg
	Extension (1m)	371015	20kg	Ø 670mm	500mm	1000mm	
	Extension	371003	6kg	Ø 680mm	250mm		

\*HGV loading achievable (suitable cover and slab to be provided by others).